

IN THE CLAIMS

Please amend the claims as follows:

Claim 1 (Currently Amended): A single carrier/DS-CDMA packet transmission method that expands a bandwidth of information symbols by a sequence of spreading codes, and transmits packets by use of spreading signals having an expanded bandwidth, comprising:

assigning a predetermined fixed time slot in a data frame for dedicated use for transmission of a reservation demand packet, the reservation demand packet being a request for an allocation of a spreading code and/or a time slot; ~~transmission and~~

assigning, in said data frame, slots other than the predetermined fixed time slot for a transmission of data packets;

code-multiplexing said data frame with one of the spreading codes so as to code-multiplex information in the predetermined fixed time slot and information in the slots other than the predetermined fixed time slot by utilizing part or all of the spreading codes; and

time-multiplexing and transmitting the code-multiplexed data frame containing the reservation demand packets by use of the predetermined fixed time slot packet and data packets by use of other time slots.

Claim 2 (Currently Amended): A single carrier/DS-CDMA packet transmission method that expands a bandwidth of information symbols by a sequence of spreading codes, and transmits packets by use of spreading signals having an expanded bandwidth, comprising:

assigning one of k ($0 < k < N$) spreading codes among ~~all~~ N total spreading codes as a fixed codes-code for dedicated use for reservation demand packet transmission, the

reservation demand packet being a request for an allocation of a spreading code and/or a time slot,

assigning another one of the k ($0 < k < N$) spreading codes as a fixed code for dedicated use for data packet transmission, and

time-multiplexing and transmitting the reservation demand packets packet encoded with the one of the k ($0 < k < N$) spreading codes and the data packet encoded with the another one of the k ($0 < k < N$) spreading codes. ~~by use of the k spreading codes and data packets by use of other spreading codes.~~

Claim 3 (Previously Presented): The packet transmission method as claimed in claim 1, wherein reservation demand packet transmission admission probability determined in advance is lowered when a channel occupancy rate of the data packets exceeds a predetermined value.

Claim 4 (Original): The packet transmission method as claimed in claim 2, wherein the spreading codes assigned to the reservation demand packet transmission are decreased in number, and the spreading codes assigned to data-packet transmission are increased in number when a channel occupancy rate of the data packets exceeds a predetermined value.

Claim 5 (Original): The packet transmission method as claimed in claim 2, wherein the reservation demand packet transmission admission probability determined in advance is lowered first when a channel occupancy rate of the data packets exceeds a predetermined value, and, subsequently, the spreading codes assigned to the reservation demand packet transmission are decreased in number while the spreading codes assigned to data-packet transmission are increased in number when the channel occupancy rate of the data packets

still exceeds the predetermined value even after the reservation demand packet transmission admission probability is lowered.

Claim 6 (Previously Presented): The packet transmission method as claimed in claim 2, wherein the spreading codes assigned to the reservation demand packet transmission are decreased in number first when a channel occupancy rate of the data packets exceeds a predetermined value, and, subsequently, the reservation demand packet transmission admission probability determined in advance is lowered if the channel occupancy rate of the data packets still exceeds the predetermined value even after the spreading codes assigned to the reservation demand packet transmission were decreased in number.

Claim 7 (Previously Presented): A mobile-radio packet transmission method using the packet transmission method of claim 3, wherein a base station measures the channel occupancy rate of the data packet, and determines the reservation demand packet transmission admission probability and a number indicative of how many spreading codes are available for the reservation demand packets.

Claim 8 (Currently Amended): The mobile-radio packet transmission method as ~~elaimed in~~ of claim 7, wherein the base station inserts the number of spreading codes available for the reservation demand packets and the reservation demand packet transmission admission probability into an information channel of a downlink by time-sharing.

Claim 9 (Cancelled):

Claim 10 (Cancelled):

Claim 11 (Currently Amended): A single carrier/DS-CDMA packet transmission system, having comprising:

a base station and a ~~plurality of mobile stations~~mobile station, wherein the base station ~~assigns~~is configured

to assign a predetermined fixed time slot in a data frame for dedicated use for transmission of a reservation demand packet, the reservation demand packet being a request for an allocation of a spreading code and/or a time slot, and

~~transmission and code multiplexing the predetermined time slot by utilizing part or all of the spreading codes,~~

to assign, in said data frame, slots other than the predetermined fixed time slot for a transmission of data packets; and

the mobile station is configured

to code-multiplex information in the predetermined fixed time slot and information in the slots other than the predetermined fixed time slot with one of the spreading codes and

to transmit the data frame containing the reservation demand packet and data packets.

~~time multiplexes and transmits a reservation demand packet in the assigned time slot and data packets in other time slots.~~

Claim 12 (Currently Amended): A single carrier/DS-CDMA packet transmission system, having comprising:

a base station and a ~~plurality of mobile stations~~mobile station, wherein

the base station ~~assigns~~ is configured
to assign one of k ($0 < k < N$) spreading codes among all N total spreading codes
as a fixed codes-code for dedicated use for reservation demand packet transmission,
the reservation demand packet being a request for an allocation of a spreading code
and/or a time slot, and notifies
to assign another one of the k ($0 < k < N$) spreading codes as a fixed code for
dedicated use for data packet transmission, and
to notify a-the mobile station of an assigned reservation demand packet
channel; and
the mobile station ~~transmits~~ is configured to transmit a reservation demand packet via
the one of k ($0 < k < N$) spreading codes and data packets via ~~either~~ the another one of the k
($0 < k < N$) spreading codes.

Claim 13 (Previously Presented): A single carrier/DS-CDMA packet transmission system comprising a base station and a plurality of mobile stations, wherein the base station comprises:

a measurement unit configured to measure a channel occupancy rate of a data packet;
and

a unit configured to determine a reservation demand packet transmission admission probability and a number indicative of how many spreading codes are available for reservation demand packets for notification to the mobile station,

wherein the base station determines the number of spreading codes available for reservation demand packets and the reservation demand packet transmission admission probability based on the measurement by the measurement unit, and notifies the mobile

station of the determined number of spreading codes and the determined admission probability through a downlink broadcast channel by time-multiplexing.

Claim 14 (Withdrawn): An uplink packet transmission method in a multi-carrier/DS-SS-CDMA mobile communication system having n (n being a natural number equal to or more than two) subcarriers, comprising:

setting up frames that define constant intervals in each communication channel of the subcarriers, and further setting up time slots by temporally dividing each of the frames into F pieces (F being a natural number equal to or more than two), and

spreading, in a mobile station, a packet to be transmitted by spreading codes in synchronization with timing of the time slots, and transmitting the packet to the base station.

Claim 15 (Withdrawn): The uplink packet transmission method as claimed in claim 14,

said mobile station requiring said base station to assign time slots and spreading codes by transmitting a reservation demand packet as preparation for packet transmission,

said base station assigning time slots and spreading codes to the mobile station that demanded, and

said mobile station spreading the packet by the assigned spreading codes and transmitting the packet via the time slots assigned by said base station.

Claim 16 (Withdrawn): The uplink packet transmission method as claimed in claim 14, wherein said mobile station makes random access to one of time slots of the communication channels to transmit a packet, without requiring the base station to assign time slots.

Claim 17 (Withdrawn): The uplink packet transmission method as claimed in claim 14, wherein said mobile station changes transmission speed of the mobile station according to a transmission volume of a packet that the mobile station is to transmit.

Claim 18 (Withdrawn): The uplink packet transmission method as claimed in claim 15,

said base station assigning k_1 (k_1 being a natural number, and $k_1 \leq F_n$) time slots for the reservation demand packet transmission, and further assigning m_1 (m_1 being a natural number, $m_1 \leq$ a total number of available spreading codes) spreading codes for spreading the reservation demand packet, and

said mobile station spreading and transmitting the reservation demand packet by one of the assigned spreading codes in the assigned time slots.

Claim 19 (Withdrawn): The uplink packet transmission method as claimed in claim 18, wherein said base station changes the number k_1 of the time slots for the reservation demand packet transmission according to the number of reservation demand packets sent from the mobile station during a predetermined period.

Claim 20 (Withdrawn): The uplink packet transmission method as claimed in claim 18, wherein said base station changes the number m_1 of the spreading codes for the reservation demand packet transmission according to the number of reservation demand packets sent from the mobile station during a predetermined period.

Claim 21 (Withdrawn): The uplink packet transmission method as claimed in claim 18, wherein said base station changes the number k_1 of the time slots for the reservation demand packet transmission and the number m_1 of the spreading codes for the reservation demand packet transmission according to the number of reservation demand packets sent from the mobile station during a predetermined period.

Claim 22 (Withdrawn): The uplink packet transmission method as claimed in claim 18, wherein the base station notifies the base station of a transmission limit of the reservation demand packet when numerous reservation demand packets are received from the mobile stations during a predetermined period, and the mobile station transmits the reservation demand packet according to the limit.

Claim 23 (Withdrawn): The uplink packet transmission method as claimed in claim 16, wherein said base station assigns k_2 (k_2 being a natural number, and $k_2 \leq F_n$) time slots as usable for packet transmission through random accessing by the mobile station, and further assigns m_2 (m_2 being a natural number, and $m_2 \leq$ a total number of available spreading codes) spreading codes for spreading a random access packet, and wherein the mobile station spreads a random access packet by one of the assigned spreading codes and transmits the packet in the assigned time slots.

Claim 24 (Withdrawn): The uplink packet transmission method as claimed in claim 23, wherein the base station changes the number k_2 of the time slots for the random access packet transmission according to the number of random access packets sent from the mobile station during a predetermined period.

Claim 25 (Withdrawn): The uplink packet transmission method as claimed in claim 23, wherein the base station changes the number m_2 of the spreading codes for the random access packet transmission according to the number of random access packets sent from the mobile station during a predetermined period.

Claim 26 (Withdrawn): The uplink packet transmission method as claimed in claim 23, wherein the base station changes the number k_2 of the time slots for the random access packet transmission and the number m_2 of the spreading codes for the random access packet transmission according to the number of random access packets sent from the mobile station during a predetermined period.

Claim 27 (Withdrawn): The uplink packet transmission method as claimed in claim 23, wherein the base station notifies the base station of a transmission limit of random access packets when numerous random access packets are received from the mobile stations during a predetermined period, and the mobile station makes random accesses according to the limit.

Claim 28 (Withdrawn): The uplink packet transmission method as claimed in claim 17, wherein the base station assigns p spreading codes (p being a natural number, and $p \leq a$ total number of available spreading codes) to the mobile station according to a transmission volume of the mobile station.

Claim 29 (Withdrawn): The uplink packet transmission method as claimed in claim 17, wherein the base station assigns to the mobile station a spreading code having a spreading factor that varies according to a transmission volume of the mobile station.

Claim 30 (Withdrawn): The uplink packet transmission method as claimed in claim 17, wherein the base station assigns q time slots (q being a natural number, and $q \leq F_n$) to the mobile station according to a transmission volume of the mobile station.

Claim 31 (Withdrawn): The uplink packet transmission method as claimed in claim 17, wherein the base station performs assigning by changing at least two of a number p of spreading codes (p being a natural number, and $p \leq$ a total number of available spreading codes), spreading codes having different spreading factors, and a number q of time slots q (q being a natural number and $q \leq F_n$) according to a transmission volume of the mobile station.

Claim 32 (Withdrawn): A downlink channel structure in a multi-carrier/DS-CDMA mobile communication system that expands a bandwidth of information symbols by a sequence of spreading codes and transmits spreading information signal obtained by the bandwidth expansion by using a plurality of subcarriers having predetermined frequency intervals, wherein

a plurality of communication channels assigned to the respective subcarriers are divided into predetermined time frames and multiplexed, and

the plurality of communication channels assigned to the respective subcarriers are configured to include a common-control channel shared by a plurality of users and communication channels specific to the respective users.

Claim 33 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in claim 32, wherein the common-control channel includes information for controlling each user's uplink transmission.

Claim 34 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in claim 32, wherein the common-control channel includes information about a response to each user's uplink transmission.

Claim 35 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in Claim 32, wherein the common-control channel includes broadcast information commonly directed to each user.

Claim 36 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in Claim 32, wherein the common-control channel includes a pilot symbol used for demodulating a received signal by each user.

Claim 37 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in Claim 32, wherein the common-control channel is assigned to one or more code channels in part or all of the subcarriers.

Claim 38 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in Claim 32, wherein the common-control channel includes different kinds of information for different subcarriers.

Claim 39 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in Claim 32, wherein information includes in the common-control channel assigned to each subcarrier is time-multiplexed to part of each time frame.

Claim 40 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in claim 39, wherein the information included in the common-control channel assigned to each subcarrier is time-multiplexed to an identical timing portion of each time frame of each subcarrier.

Claim 41 (Withdrawn): The downlink channel structure in the multi-carrier/DS-CDMA mobile communication system as claimed in claim 39, wherein the information included in the common-control channel assigned to each subcarrier is time-multiplexed to different timing portions of each time frame of each subcarrier.